

GENERAL INFORMATION

INVINO-1062 is defoamer prepared by a variety of polyetherol, silicone grease and other low-surface active integriant. INVINO-1062 has excellent stability at wide range of temperature, which can well control the bubble in the delayed coking process, and at the same time improve the equipment utilization without affecting the quality of the oil output oil.

TECHENICAL DATA SHEET

Appearance	Light yellow transparent liquid
Ionic Type of Emulsion	Nonionic
PH	6.0-8.0
Solid Content (%)	10.0±1.0
Viscosity (cps)	100-200

APPLICATIONS

- Delayed coking

KEY PROPERTIES

- Good high temperature stability, suitable for high temperature system
- Quickly eliminate foam and suppress foam for a long time
- Low silicon product, does not affect the output oil

LEVELS OF USE

- INVINO-1062 can be used directly or after dilution.
- It is recommended to use a metering pump for continuous addition. Generally speaking, the recommended addition amount is 0.01~0.3% to effectively eliminate and prevent the regeneration of foam, but the optimal addition amount should be determined through on-site debugging.

HANDLING AND STORAGE

- Avoid any eye and skin contact.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



INVINO-1062



Technical Data Sheet

- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

PACKAGE

- Net Weight: 25kgs,200kgs/Plastic Drum, IBC

SHELF LIFE

- INVINO-1062 has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Nanjing Invelychem Co., Ltd

Factory Address

No. 55. XINHAI Avenue, XUYI District, HUIAN, China.

Tel: +86 25 58717026

