

GENERAL INFORMATION

INVINO-1080 consists of special polyether silicon, silicone grease, fumed silica and emulsifiers. It can effectively control the stable foam formed by the minerals, organic matter, and foam agents in the process of drainage and gas collection. It has the characteristics of "three resistance" of oil resistance, acid and alkali, and mineralization.

TECHENICAL DATA SHEET

Appearance	Emulsion
Ionic Type of Emulsion	Weak anion
PH	7.0-9.0
Viscosity (cps)	800-2000
Density (g/cm³, 25°C)	1.0-1.1

APPLICATIONS

- In the process of drainage and gas collection

KEY PROPERTIES

- The foaming speed is fast, the bubble is strong, and the amount is small.
- Differentiations are excellent.
- Non -toxic and high safety.

LEVELS OF USE

- Add point: The air pipeline or gas collecting station exchange pipeline;
- Add method: Intermittently impacts or continuously submit or measuring pump continuous investment;
- Add dose: 0.01%-0.5%.

HANDLING AND STORAGE

- Avoid any eye and skin contact.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



INVINO-1080



Technical Data Sheet

- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

PACKAGE

- Net Weight: 25kgs,200kgs/Plastic Drum, IBC

SHELF LIFE

- INVINO-1080 has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Nanjing Invelychem Co., Ltd

Factory Address

No. 55. XINHAI Avenue, XUYI District, HUIAN, China.

Tel: +86 25 58717026

