INVINO-1730

Technical Data Sheet



GENERAL INFORMATION

INVINO-1730 is a modified polysiloxane defoamer, extensively used in alkanolamine gas scrubbing systems, exhibit excellent anti-foaming and defoaming property.

TECHENICAL DATA SHEET

Appearance	White Emulsion
Ionic Type of Emulsion	Weak anion
PH	6.0-8.0
Solid Content (%)	20.0±1.0
Viscosity (cps)	1000-5000

APPLICATIONS

• Desulfurization and decarbonization of natural gas (amine unit)

KEY PROPERTIES

- Quick defoaming
- Excellent stability
- Excellent resistance to alkali, temperature and shear resistance

LEVELS OF USE

- INVINO-1730 can be used directly in the production process or diluted.
- The addition amount range is 0.5-100ppm. due to different application system, it is recommended to test in advance to achieve the best defoaming effect.

HANDLING AND STORAGE

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



INVINO-1730

Technical Data Sheet



• For further information please check to MSDS.

PACKAGE

• Net Weight: 25kgs,200kgs/Plastic Drum, IBC

SHELF LIFE

• INVINO-1730 has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

