

GENERAL INFORMATION

INVINO-2430 is a highly effective defoaming agent for aqueous systems. It has rapid defoaming efficacy in a wide range of pH and temperature, and has a long-lasting antifoaming effect.

TECHENICAL DATA SHEET

Type	Silicone defoamer
Appearance	White Emulsion
Ionic Type of Emulsion	Weak anion
PH	6.0-8.0
Solid Content (%)	30.0±1.0
Viscosity (cps)	1000-5000

APPLICATIONS

- General water treatment system
- Papermaking engineering
- Wastewater treatment
- Industrial cleaning

KEY PROPERTIES

- Easy to disperse in water
- Excellent defoaming durability
- Wide range of applications
- Ultrafiltration membrane system available

LEVELS OF USE

- Add INVINO-2430 directly to the foaming system to ensure uniform dispersion.
- It can be used directly in the production process or diluted. It is recommended to use a metering pump for continuous addition.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



Technical Data Sheet

- Generally speaking, an addition amount of 100~1000ppm can effectively control the foam in the production process.
- According to different production processes, the optimal addition amount should be determined through on-site testing.

HANDLING AND STORAGE

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

PACKAGE

- Net Weight: 25kgs,200kgs/Plastic Drum, IBC

SHELF LIFE

- INVINO-2430 has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

