

GENERAL INFORMATION

INVINO-3001 is a kind of non-silicon defoamer with mineral oil as main material, supplemented by polyether and nonionic surfactant.

TECHENICAL DATA SHEET

| | |
|-------------------------------------|----------------------------|
| Ingredient | Mineral Oil |
| Appearance | Amber opaque turbid liquid |
| Density (g/cm ³ , 25°C): | 0.85-0.95 |
| Viscosity (25degree) | 100-2000 |
| Dispersity | Soluble in Water |
| Active substance | 99%min |

APPLICATIONS

- PVC water-based paint and inks.
- Architectural coatings

KEY PROPERTIES

- Excellent compatibility.
- Can't lead shrinkage cavity when used in production.
- Leveling in paint.

LEVELS OF USE

- 0.2-0.6% based on total formulation with sufficient mixing.
- Add INVINO-3001 for two times, one time is during the grinding of the pigment, and the other during formulating the coating.

HANDLING AND STORAGE

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.





PACKAGE

- Net Weight: 25kgs,180kgs/Plastic Drum,850kgs

SHELF LIFE

- INVINO-3001 has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!



Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Nanjing Invelychem Co., Ltd

Factory Address

No. 55. XINHAI Avenue, XUYI District, HUAIAN, China.

Tel: +86 25 58717026

