

GENERAL INFORMATION

INVINO-3200 is a 100% active liquid defoamer. Developed specifically for emulsion adhesives, it is optimized for high efficiency, durability and compatibility, and the product has proven to be effective in certain applications.

TECHENICAL DATA SHEET

| | |
|---------------------------------------|--|
| Ingredient | Mineral Oil |
| Appearance | Light yellow or amber opaque turbid liquid |
| Density(g/cm³, 25℃) | 0.85-0.95 |
| Viscosity (25degree) | 100-2000 |
| Dispersity | Soluble in Water |
| Active substance | 99%min |

APPLICATIONS

- Emulsion type adhesive, latex paint and pressure sensitive adhesive
- Waterborne coatings and inks

KEY PROPERTIES

- Broad spectrum - Good defoaming effect in various types of emulsion adhesives, coatings and inks.
- Persistence - Not only effective during storage, but also under continuous pumping conditions.
- Compatibility - Defoamer has good compatibility, does not produce oil slick, does not produce fish eyes in transparent film

LEVELS OF USE

- 0.2-0.6% based on total formulation with sufficient mixing
- Add INVINO-3200 for two times, one time is during the grinding of the pigment, and the other during formulating the coating.

HANDLING AND STORAGE

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



Technical Data Sheet

- Stored between 0°C-40°C.
- For further information please check to MSDS.

PACKAGE

- Net Weight: 25kgs,180kgs/Plastic Drum,850kgs.

SHELF LIFE

- INVINO-3200 has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Nanjing Invelychem Co., Ltd
Factory Address
No. 55. XINHAI Avenue, XUYI District, HUAIAN, China.
Tel: +86 25 58717026

