Technical Data Sheet



GENERAL INFORMATION

INVINO-5023 is mixture products which polymer chemical as major raw material with modified polysiloxane, extensively used in aqueous system, exhibit excellent anti-foaming and defoaming property.

TECHENICAL DATA SHEET

Туре	Modified silicone defoamer
Appearance	White Emulsion
Density(25°C,g/cm³)	0.9-1.0
PH	6.0-8.0
Viscosity (cps)	1000-5000

APPLICATIONS

- Paper coating.
- Production of rosin gum sizing agent;
- Latex paint, latex, such as aqueous solution of polyvinyl alcohol; emulsion of styrene-acrylic, pure-propyl,
- Water treatment industry with strong acid and alkali.
- Industries which Silicone emulsion can't work well.

KEY PROPERTIES

- Good compatibility
- Excellent dynamic defoaming and anti-foaming performance
- Suitable for a variety of resin systems

LEVELS OF USE

• 0.05-0.1g/l based on total formulation with sufficient mixing.

HANDLING AND STORAGE

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



Factory Address

No. 55. XINHAI Avenue, XUYI District, HUAIAN, China.

Tel: +86 25 58717026



INVINO-5023

Technical Data Sheet



- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

PACKAGE

• Net Weight: 25kgs,200kgs/Plastic Drum, IBC.

SHELF LIFE

• Shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



Tel: +86 25 58717026