

GENERAL INFORMATION

INVINO-530D is a polyether modified silicone defoamer

TECHENICAL DATA SHEET

Appearance	White Emulsion
Ionic Type of Emulsion	Weak anion
PH	6.0-8.0
Solid Content (%)	30.0±1.0
Viscosity (cps)	1000-5000

APPLICATIONS

- Extraction and evaporation process
- Fermentation process of molasses
- Other fermentation processes

KEY PROPERTIES

- Maintains excellent durability at low addition amount
- Good compatibility
- Excellent dynamic defoaming and anti-foaming performance. Applicable to a variety of foaming systems
- No side effects

LEVELS OF USE

- INVINO-530D can be directly added to the system that needs defoaming.
- The general addition amount is 10-1000ppm. For different defoaming systems, due to different usage environments, it is recommended to conduct tests in advance to achieve the best defoaming effect and control the appropriate dosage. According to different production processes, the optimal addition amount should be determined through on-site testing.

HANDLING AND STORAGE

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



Technical Data Sheet

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

PACKAGE

- Net Weight: 25kgs,200kgs/Plastic Drum, IBC

SHELF LIFE

- INVINO-530D has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Nanjing Invelychem Co., Ltd
Factory Address
No. 55. XINHAI Avenue, XUYI District, HUAIAN, China.
Tel: +86 25 58717026

