

GENERAL INFORMATION

INVINO-6225 is a modified polysiloxane defoamer, extensively used in the circuit board cleaning, pesticide, waste water in anion/non-ionic surfactant active system, exhibit excellent anti-foaming and defoaming property.

TECHENICAL DATA SHEET

Type	Silicone defoamer
Appearance	White Emulsion
Ionic Type of Emulsion	Weak anion
PH	6.0-8.0
Solid Content (%)	20.0±1.0
Viscosity (cps)	1000-5000

APPLICATIONS

- Agrochemical-Suspension Emulsion.
- Liquid detergent

KEY PROPERTIES

- Easy to disperse in water
- Easy to use
- Wide pH and temperature range
- Quick defoaming

LEVELS OF USE

- Add INVINO-6225 directly to the foaming system, ensuring uniform dispersion. For high-temperature foaming systems (>60°C), it is recommended to add INVINO-6225 before reaching 60°C and disperse it evenly to achieve optimal performance.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



Technical Data Sheet

- Based on factors such as viscosity, temperature, and agitation of different foaming systems, the most cost-effective dosage should be determined in increments of 10 ppm. Generally, a dosage of 30-200 ppm ensures an ideal defoaming effect.
- In certain industries, such as coatings and biological fermentation, a higher dosage of 2-5% may be required.

HANDLING AND STORAGE

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

PACKAGE

- Net Weight: 25kgs,200kgs/Plastic Drum, IBC

SHELF LIFE

- INVINO-6225 has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

