

## GENERAL INFORMATION

---

INVINO-8062 is a non-silicone defoamer based on functional modified polyether, with dispersibility and strong dynamic defoaming ability. It is suitable for defoaming of white water in papermaking process at hightemperature.

## TECHENICAL DATA SHEET

|                 |                                   |
|-----------------|-----------------------------------|
| Appearance      | Light yellow to colourless liquid |
| PH              | 5.0-9.0                           |
| Viscosity (cps) | 100-1000                          |

## APPLICATIONS

---

- Papermaking.
- Waste water treatment.
- High-temperature processing.

## KEY PROPERTIES

---

- NP and APEO are not included in the material components;
- INVINO-8062 can be used within a strong alkali environment (pH 12.0) with better anti-foaming performance;
- Good compatibility with the application system and strong foam suppression performance.

## LEVELS OF USE

---

- Generally speaking, an addition amount of 100~1000ppm can effectively control the foam in the production process.
- Depending on the different production processes, the optimal addition amount should be determined through on-site testing.

## HANDING AND STORAGE

---

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



## Technical Data Sheet

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

## PACKAGE

---

- Net Weight: 200kgs/Plastic Drum,IBC

## SHELF LIFE

---

- INVINO-8062 has a shelf life of 12 months from date of manufacture.

## QUALITY ASSURANCE

---

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

**Nanjing Invelychem Co., Ltd**

Factory Address

No. 55. XINHAI Avenue, XUYI District, HUAIAN, China.

Tel: +86 25 58717026

