

Technical Data Sheet

GENERAL INFORMATION

G10 is a 100% active liquid defoamer, with excellent dynamic defoaming, foam suppression performance and long-lasting defoaming ability.

TECHNICAL DATA SHEET

Appearance	White Emulsion
Ionic Type of Emulsion	Weak anion
PH	6.0-8.0
Solid Content (%)	30.0±1.0
Viscosity (cps)	1000-5000

APPLICATIONS

- Various latex paints
- Emulsified coatings such as acrylic acid, vinyl acetate, acrylic acid, styrene acrylic, copolymers, etc.
- Various emulsion-based water-based pressure sensitive adhesives, coatings and inks.

KEY PROPERTIES

- Excellent system compatibility
- Long-term storage stability
- Both fast defoaming and long-lasting antifoam

LEVELS OF USE

- Can be added directly during the manufacturing process, or after pre-dispersion
- Addition amount of 0.2%-0.3% of the total formula can effectively extinguish and prevent the regeneration of foam.
- Modifying the dosage according to different systems,

HANDLING AND STORAGE

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Nanjing Invelychem Co., Ltd

Factory Address

No. 55. XINHAI Avenue, XUYI District, HUAIAN, China.

Tel: +86 25 58717026



Technical Data Sheet

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

PACKAGE

- Net Weight: 25kgs,200kgs/Plastic Drum, IBC

SHELF LIFE

- INVINO-G10 has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Nanjing Invelychem Co., Ltd

Factory Address

No. 55. XINHAI Avenue, XUYI District, HUAIAN, China.

Tel: +86 25 58717026

