

## COMPOSITION

---

- Polydimethylsiloxane
- Food grade non-ionic surfactants
- Purified water

## TECHENICAL DATA SHEET

<b>Appearance</b>	Milky white viscous liquid
<b>Activity Solid (%)</b>	40.0 ± 1.0
<b>PH</b>	6.0-8.0
<b>Viscosity (cps)</b>	200-2000
<b>Stability</b>	Unstratified based on 3000 rpm /30 minutes

## APPLICATIONS

---

- Fermentation industries such as glutamic acid, gentamicin, and avermectin
- Yeast fermentation

## KEY PROPERTIES

---

- Low dosage
- Fast defoaming speed
- Long foam inhibition time
- Odourless, non-toxic side effects and good acid and alkali resistance
- Workable up to 130 degrees

## LEVELS OF USE

---

- INVINO-F3240 can be directly added to the base material and also be used as supplementary material in the later stage.
- INVINO-F3240 is recommended to mix with polyether at a ratio of 1:1, stir and sterilize, and

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



## Technical Data Sheet

then add supplementary material; the usage amount is about 0.5-1%.

## HANDLING AND STORAGE

---

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

## PACKAGE

---

- Net Weight: 25kgs,200kgs/Plastic Drum, IBC

## SHELF LIFE

---

- INVINO-F3240 has a shelf life of 12 months from date of manufacture.

## QUALITY ASSURANCE

---

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

