

COMPOSITION

- Polydimethylsiloxane
- Food grade non-ionic surfactants
- Dispersant
- Purified water

TECHENICAL DATA SHEET

Appearance	Milky white viscous liquid
Activity Solid (%)	30.0±2.0
PH	6.0-8.0
Viscosity (cps)	200-2000
Stability	Unstratified based on 3000 rpm /30 minutes

APPLICATIONS

- Food processing
- Soybean processing,
- Starch
- Dairy and beverage industries.
- Glutamate, gentamicin, abamycin and other fermentation industries.

KEY PROPERTIES

- Low dosage,
- Fast defoaming speed,
- Long foam inhibition time,
- Odourless, non-toxic side effects and good acid and alkali resistance.
- Workable up to 130 degrees

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



Technical Data Sheet

LEVELS OF USE

- INVINO-F380 can be diluted to a homogeneous solution with water or foaming solution and then added to the foaming solution, or can be added directly.
- The recommend dosage is 0.01%-1%, depending on the application.
- INVINO-F380 can be added directly and also be fed into the irrigation for two times at a later stage. It is recommended to mix and sterilize it with polyether at a ratio of 1:1 and then add the feed

HANDLING AND STORAGE

- Avoid any eye and skin contact.
- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

PACKAGE

- Net Weight: 25kgs,200kgs/Plastic Drum, IBC

SHELF LIFE

- INVINO-F380 has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

