

GENERAL INFORMATION

INVINO-8082A is a non-silicone defoamer based on functional modified polyether, developed as an improved version of INVINO-8082, featuring excellent dispersibility and strong dynamic defoaming performance. It is compatible with both acidic and alkaline systems and is also qualified for use in size press applications.

TECHENICAL DATA SHEET

Appearance	Yellowish to light brown liquid
PH	5.0-9.0
Viscosity (cps)	100-1000

APPLICATIONS

- Sizing processing in the paper industry
- High-temperature processing and in systems with extreme pH values.

KEY PROPERTIES

- NP and APEO are not included in the material components;
- INVINO-8082A can be used within a strong alkali environment (pH 12.0) with better anti-foaming performance;
- Good compatibility with the application system and strong foam suppression performance.

LEVELS OF USE

- Generally speaking, an addition amount of 100~1000ppm can effectively control the foam in the production process.
- Depending on the different production processes, the optimal addition amount should be determined through on-site testing.

HANDING AND STORAGE

- Avoid any eye and skin contact.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.



INVINO-8082A



Technical Data Sheet

- Keep away from source of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C-40°C.
- For further information please check to MSDS.

PACKAGE

- Net Weight: 200kgs/Plastic Drum,IBC

SHELF LIFE

- INVINO-8082A has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

We guarantee that all operations are conducted according to the stipulated standards. If you have any questions when you use. Please don't hesitate to contact us!

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Nanjing Invelychem Co., Ltd
Factory Address
No. 55. XINHAI Avenue, XUYI District, HUIAN, China.
Tel: +86 25 58717026

