

Silicone Defoamer — INVINO 424

Mixture of Defoaming Polysiloxane and Fumed Silica in Polyether

Overview

INVINO 424 is a mixture of defoaming polysiloxane and fumed silica in polyether. It contains no VOC, offers excellent compatibility, and good foam-suppression characteristics. Under stirring conditions, it can be added at any stage of production. Recommended for waterborne latex paints, printing inks, overprint varnishes, and emulsion adhesives.

Product Characteristics

Type: Polyether-modified polysiloxane mixture, containing fumed silica

Application Systems and Dosage

- Stir gently (low shear) before use
- The long-term efficacy of the defoamer depends on the system and should be tested in different formulations (testing at different temperatures is recommended)
- Dosage based on total formulation as supplied: 0.2–2.0%

Physical and Chemical Properties

Property	Reference Value
Appearance	Clear to slightly turbid liquid
Non-volatile content	ca. 100%

Packaging

- 25 KG/drum
- 200 KG/drum
- 1000 KG IBC

Storage Stability

When stored in the original unopened container at +4 to +40°C, the product has a shelf life of at least 12 months from the date of manufacture.

Note: This technical data sheet is intended to provide basic product information to technicians in coatings, inks, and related fields, for R&D reference only. It does not constitute any warranty. Please pre-test for suitability.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Nanjing Invelychem Co., Ltd

2nd Floor of 3rd Building, No.18 Jialingjiang East Street,
Jianye District, Nanjing, China

Tel: 0086 15335157506 | Email: info@invelydefoamer.com